

CEE-BEE CLEANER R-674

by Cee-Bee®



d a t a s h e e t

CEE-BEE CLEANER R-674 is a high performance cleaner designed to penetrate and remove oils, soils and many types of tenacious grease.

BENEFITS

- Superior penetration and solvency for grease and soil.
- Very effective jet engine gas path cleaner.
- Free rinsing. Leaves no residue when used as directed.
- Safe on all metals, including stainless steel, mild steel, aluminum and titanium.
- Contains no phenolics, phosphates or heavy metal salts.
- Surfactants biodegradable.

CONFORMS TO

- **PRATT & WHITNEY SPMC 87-6, GAS PATH CLEANER**
- **ALLISON GAS TURBINE OPERATIONS (GENERAL MOTORS CORP.)**

**NOTE: To place an order, call or FAX Customer Service at
800-932-7006 / 1-216-441-1377
Cee-Bee Cleaner R-674 Product Code #20067**



NOTES PRIOR TO HANDLING

Before using your McGean-Rohco, Inc. products, all safety and operating instructions should be read and understood. If you have any questions, please contact your McGean-Rohco representative before proceeding.

USE PROCEDURES

Jet Engine Gas Path Cleaner

Dilute cleaner with 9 parts water (deionized or demineralized water is preferred). Use the following procedure, or the procedure specified by the engine manufacturer.

1. When the engine is cool, rotate using the started with the ignition off and inject about 20 gals. of cleaner solution through the engine inlet in 5 gal. increments.
2. After injection of each 5 gal. increment, allow to dwell a few minutes.
3. When all of the cleaner solution has been sprayed through the engine, a water rinse may be use to flush out residual cleaner and soils.

Brush, Mop, or Spray on Application

Dilute cleaner with 3 to 4 parts water. For cleaning heavily soiled areas, the cleaner solution or undiluted cleaner may be mixed with up to 3 parts mineral spirits (aromatic petroleum solvent).

1. Apply cleaner solution with non-atomizing spray, mop or brush and allow to dwell until soils have been penetrated.
2. Light agitation with a stiff bristle brush will speed cleaning.
3. Rinse thoroughly with high pressure water to prevent streaking.

USE PROCEDURES (continued)

Soak Tank

1. Immerse parts in Cee-Bee R-674 diluted with 3 to 4 parts water.
2. Allow to soak until soils have been penetrated.
3. Use air or manual agitation to speed cleaning.
4. Remove parts from the tank and rinse with high pressure water.

Cleaning Aircraft Wheels

1. Immerse wheels in Cee-Bee R-674 diluted with 10-20% (vol.) Cee-Bee C-50.
2. Allow wheels to soak until soils have been penetrated and loosened.
3. Remove wheel from the tank and rinse thoroughly with high pressure water.

PROPERTIES

- Thin, clear liquid. Contains no free alkali. Flash point, 145°F., TCC.

PRECAUTIONS

- Avoid contact with eyes and skin. Wear rubber gloves and face shield or safety glasses. Use with adequate ventilation. Do not take internally.
- In case of accidental contact, flood with water. If eye irritation persists, seek medical attention.
- Do not use cleaner at temperature above 140°F.
- Do not use undiluted cleaner on painted surfaces since some discoloration may occur.

PRECAUTIONS (continued)

- Avoid eye and skin contact. Wear rubber gloves and face shield or safety glasses. Contains petroleum solvent. Do not use in confined areas or at temperature above 120°F. Use with adequate ventilation.
- Do not take internally. For contact, flood with water. If eye irritation persists, seek medical attention. Avoid splashing nearby personnel if spray rinse is used.

Copyright 1994 McGean-Rohco, Inc.
Rev. 2/01