

# CEE-BEE STRIPPER A-202

by Cee-Bee®



## data sheet

**CEE-BEE STRIPPER A-202** is a viscous, acid/phenolic stripper for bond release removal of polyurethane, epoxy, and other chemically resistant coatings, including base coats and primers.

### BENEFITS

- Effective and rapid removal of chemically resistant coatings.
- Evaporation retardant added to keep stripper “wet” for long dwell times on resistant coatings.
- Excellent cling to vertical and overhead surfaces.
- Rinses off easily even with cold water.
- Safe on aluminum, copper, mild-steel and stainless steel.
- Low phenolic content. Non-flammable.
- Surfactants biodegradable.

### CONFORMS TO

- **BOEING BAC 5725**
- **BOMBARDIER BAPS 180-006**
- **DOUGLAS DPM 5619**
- **FEDERAL EXPRESS**
- **GENERAL ELECTRIC C04-022**
- **GREENWICH AIRMOTIVE**
- **LOCKHEED EPS 32.2420**

**NOTE: To place an order, call or FAX Customer Service at  
800-932-7006 / Fax 1-216-441-1377  
Cee-Bee Stripper A-202 Product Code #23014**



## NOTES PRIOR TO HANDLING:

Before using any Cee-Bee products, all safety and operating instructions should be read and understood. If you have any questions, please contact your Cee-Bee representative before proceeding.

## USE PROCEDURES

- Surface should be dry and <80°F (26°C) for optimum stripping.
- Apply Cee-Bee A-202 with non-atomizing spray, brush or flow on. Allow stripper to dwell until coating is wrinkled and loosened. Agitate lightly. For questions regarding a suitable spray nozzle, please contact your Cee-Bee representative.
- Reapply stripper to areas not completely released from the substrate and allow to dwell.
- When stripping is complete, rinse off with a high pressure water spray.

## PROPERTIES

- Viscous, amber liquid with a pungent odor.
- pH below 2. No flash point.

## PRECAUTIONS

- **DANGER!** Rapidly absorbed through the skin. May be fatal if exposure is extensive.
- Can cause severe burns. Avoid all contact with eyes and skin. Wear rubber gloves and goggles or face shield. Use full wash rack gear for large scale operations.
- Avoid breathing vapors. Provide adequate ventilation.

**PRECAUTIONS (continued)**

- **DO NOT** take internally.
- Wash after handling. In case of accidental contact, immediately flood with water while removing contaminated clothing. Obtain medical attention.
- For inhalation, remove to fresh air.
- Damaging to magnesium, high strength steel, acrylic and most plastics.
- Keep bung tight to prevent leakage. Before removing bung, loosen slowly to relieve internal pressure to avoid spewing of contents.