

CEE-BEE STRIPPER R-206

by Cee-Bee®



d a t a s h e e t

CEE-BEE STRIPPER R-206 is a viscous, non-phenolic, acid-activated stripper for bond release removal of epoxy and polyurethane and other chemically resistant coatings.

BENEFITS

- Effective and rapid removal of chemically resistant coatings.
- Evaporation retardant added to keep stripper “wet” for long dwell times on resistant coatings.
- Excellent cling to vertical and overhead surfaces.
- Rinses off easily even with cold water.
- Safe on aluminum, copper, mild steel and stainless steel.
- Surfactants biodegradable. No phenols, cyanides or heavy metals.

CONFORMS TO

- MIL-R-81903, TYPE II, CLASS 2 (QPL)

**NOTE: To place an order, call or FAX Customer Service at
800-327-0466 / FAX 1-216-441-1377
Cee-Bee Stripper R-206 Product Code # 23120**



NOTES PRIOR TO HANDLING

Before using your McGean-Rohco, Inc. products, all safety and operating instructions should be read and understood. If you have any questions, please contact your McGean-Rohco representative before proceeding.

USE PROCEDURES

1. Surface should be dry and below 80°F.
2. Flow on stripper or apply with non-atomizing spray, brushes or mops.
3. Allow stripper to dwell until coating wrinkles and is loosened from the surface.
4. Lightly agitate surface with mops or brushes.
5. Reapply stripper to areas not completely released.
6. When stripping action is complete, rinse thoroughly with high pressure water.

PROPERTIES

- Viscous liquid with a pungent odor. pH below 2.
- No flash point.

PRECAUTIONS

- **DANGER!** Contains methylene chloride and organic acids. If swallowed, may be fatal. Can cause severe burns.

PRECAUTIONS (continued)

- Do not breath vapors. Provide good ventilation. Use respirator in area of high vapor concentration.
- Wash after handling. For contact with eyes or skin, immediately flush with water for at least 15 minutes. Get medical attention.
- For inhalation, remove to fresh air. Call a physician.
- Damaging to magnesium, high strength steel, acrylic and most plastics.
- Keep drum bung tight to prevent leakage.
- Before removing bung, loosen slowly to relieve internal pressure to avoid spewing of contents.

Copyright 1992 McGean-Rohco, Inc.

Revd. 2/01