

# CEE-BEE E-2060 PAINT STRIPPER

by *Cee-Bee*<sup>®</sup>



## d a t a s h e e t

**CEE-BEE E-2060** is a non-toxic, hydrogen peroxide-activated paint stripper designed for removing polyurethane, epoxy and other paint systems.

### BENEFITS

- Contains no halogenated solvents, phenol or heavy metals.
- Provides excellent removal of polyurethane, epoxy and other paint systems.
- Thixotropic - Clings to vertical, inclined and overhead surfaces.
- Slow drying for maximum reaction time.

### CONFORMS TO

- **AMS 1376B**
- **BOEING D6-17487, Rev. M (except magnesium immersion corrosion)**
- **THE BOEING COMPANY DPM 5549**
- **DOUGLAS CSD-1**
- **UNITED AIRLINES (CSM 5.01)**
- **VOUGHT 208-9-151**

**NOTE: To place an order, call or FAX Customer Service at  
800-932-7006 / FAX 216-441-1377  
Cee-Bee E-2060 Product Code # 23260**



## NOTES PRIOR TO HANDLING

**Before using any Cee-Bee product, all safety and operating instructions should be read and understood. If you have any questions, please contact your Cee-Bee representative before proceeding.**

## USE PROCEDURES

### **Application:**

1. Optimum performance is attained at temperatures between 75 - 87°F (24 - 30°C).
2. The surface to be stripped should be clean and completely dry.
3. Spray an even, medium coat of stripper, starting from the bottom of the aircraft and working upward.
4. Keep the surface wet with stripper until the paint buckles.
5. When the paint is lifted, agitate the surface to remove the loosened paint.
6. Reapply stripper as required.
7. When all of the paint has been lifted, use a brush or squeegee to remove the loosened paint and residual stripper.
8. For best results, apply a mild alkaline cleaning solution (Super Bee 210, Product Code # 20080) to effectively remove paint and stripper residue.
9. Thoroughly rinse the surface with water.

### **Equipment:**

- Use a high-pressure (5:1 or 10:1) air-activated pump equipped with a 0.5 in.(1.3 cm) inside diameter high -pressure hose and spray wand with a fan-type spray nozzle.
- Use a fan-type spray nozzle (such as 2508) for this application.
- Apply the stripper using a pump inlet pressure between 80 to 110 psi.
- For questions regarding suitable pumps or spray nozzles required for this application, please contact your Cee-Bee representative.

## PROPERTIES

- Viscous liquid with a mild odor.
- No flash point.

## SAFETY & HANDLING

- Skin or eye contact can cause irritation. Chemical goggles, face shield, chemical-resistant gloves and protective clothing sufficient to avoid contact are recommended.
- In case of accidental contact, flush area thoroughly with water. If irritation persists, seek medical attention.
- Do not take internally.
- Use in well-ventilated areas.
- Do not mix with other paint strippers or materials containing chromium.
- **Do not store used stripper and removed coatings in closed container as an exothermic (severe heat) reaction may occur.**
- **Spent drums from E-2060 should be thoroughly rinsed before disposal.**
- **If used stripper is placed back into the original E-2060 drums, these drums MUST first be rinsed thoroughly and only closed with a vented cap.**