

# CEE-BEE STRIPPER R-256

by Cee-Bee®



## data sheet

**CEE-BEE STRIPPER R-256** is a high performing stripper for removing urethanes, epoxies, primers and enamels.

### BENEFITS

- Effective and economical.
- Thixotropic - clings to vertical, inclined and overhead surfaces.
- Low odor - suitable for indoor use.
- Safe on most aircraft structural metals, including high strength steel, mild steel, cadmium, aluminum, magnesium and copper alloys.
- Surfactants biodegradable.

### CONFORMS TO

- **AMS 1375**
- **BOEING D6-17487 REVISION "P"**
- **DOUGLAS CSD-1, TYPE III**
- **MIL-R-81294D, TYPE I, CLASS 1 AND CLASS 3 (QPL)**
- **MIL-R-81294D, TYPE II, CLASS 1 AND CLASS 3 (QPL)**
- **MIL-R-81294D, TYPE IV CLASS 1 AND CLASS 3 (QPL)**
- **SIKORSKY AIRCRAFT SPECIFICATION SS 8786**
- **T.O.1-1-8**

**NOTE: To place an order, call or FAX Customer Service at  
800-932-7006 / FAX 1-216-441-1377  
Cee-Bee Stripper R-256 Product Code # 23900**



## NOTES PRIOR TO HANDLING

**Before using any Cee-Bee products, all safety and operating instructions should be read and understood. If you have any questions, please contact your Cee-Bee representative before proceeding.**

## USE PROCEDURES

For optimum stripping, the surface should be dry and <80°F (26°C).

- Apply a thin, uniform film of stripper with non-atomizing spray, brush or roller. Allow to dwell until coating is penetrated and loosened. For questions regarding a suitable spray nozzle, please contact your Cee-Bee representative.
- Agitate surface with a stiff bristle brush.
- Reapply. When stripping action is complete, squeegee or scrape loosened coating and spent stripper from the surface for disposal.
- Rinse surface with high pressure water.

## PROPERTIES

- Viscous, opaque, yellow liquid. Solvent odor.
- No flash point.

## PRECAUTIONS

- **WARNING!** Contains chlorinated solvents and phenol. Rapidly absorbed through the skin. Prolonged exposure could be fatal. Avoid eye and skin contact. Contact may not be immediately apparent, therefore, wear protective clothing, such as face shields or goggles, gloves, aprons, boots, etc.
- Provide adequate ventilation. Do not take internally. For accidental contact, immediately flood area with water for at least 30 minutes. Seek prompt medical attention. Open containers slowly to avoid spewing of contents.