

CEE-BEE A-953

by Cee-Bee®



d a t a s h e e t

CEE-BEE A-953 is a thickened solvent type remover for corrosion inhibiting compounds.

BENEFITS

- Slow evaporation.
- Excellent solvency for removing corrosion inhibiting compounds, temporary coatings, grease and greasy soils as well as rubber residue from wheel hubs.
- Safe for use on most painted surfaces when used as directed.
- Low vapor toxicity. Safer than methyl ethyl ketone (MEK), toluene or xylene. Safer than the halogenated solvents. This product will not damage the earth's ozone layer.
- Contains no phenolics, cyanides, nitrates, heavy metal salts, or hazardous solvents. This product does not contain methylene chloride or any other halogenated solvent.

CONFORMS TO

- **BOEING D6-17487 REVISION "P"**
- **ASSIGNED DOUGLAS DPM 6561-1**
- **GOODRICH CORP. (WHEEL AND BRAKES)**

**NOTE: To place an order, call or FAX Customer Service at
800-327-0466 / FAX 1-216-441-1377
Cee-Bee A-953 Product Code # 24055**



NOTES PRIOR TO HANDLING

Before using your McGean-Rohco, Inc. products, all safety and operating instructions should be read and understood. If you have any questions, please contact your McGean-Rohco representative before proceeding.

USE PROCEDURES

1. Mix the contents well before using.
2. Apply cleaner with mops, brushes or non-atomizing spray. Start at the bottom and work upward to avoid streaking.
3. Allow cleaner to dwell at least 5 minutes until soils are penetrated, then agitate surface with a brush or mop.
4. Rinse thoroughly with high pressure water, starting at the top and working downward. It may require additional rinsing to avoid streaking and filming.

PROPERTIES

- Hazy liquid. Mild odor.
- High flash point, above 200° F. (93° C)

PRECAUTIONS

- Contains concentrated solvents. Avoid eye and skin contact. Use chemical resistant gloves and face shield or goggles. Some form of eye protection is always absolutely essential. Use with adequate ventilation. Do not use in confined areas.
- If ventilation is inadequate, use a niosh - certified respirator which will protect against organic vapor and dust/mist. Do not take internally. For contact with eyes or skin, flood with water. If eye irritation persists, seek medical attention. For inhalation, remove to fresh air.

PRECAUTIONS (continued)

- Store containers in a cool dry area. Open containers slowly to prevent any spewing of contents. Keep containers tightly sealed. Before using on plastic electrical insulation or a painted surface that might be damaged, check effect on samples.