

CEE-BEE A-954

by Cee-Bee®



d a t a s h e e t

CEE-BEE A-954 is a solvent type remover for corrosion inhibiting compounds.

BENEFITS

- Slow evaporation.
- Excellent solvency for removing corrosion inhibiting compounds and temporary coatings, as well as for grease and greasy soils.
- Safe for use on most painted surfaces when used as directed.
- Low vapor toxicity. Safer than methyl ethyl ketone (MEK), toluene or xylene. Safer than the halogenated solvents. This product will not damage the earth's ozone layer.
- Contains no phenolics, cyanides, nitrates, heavy metal salts, or hazardous solvents. This product does not contain methylene chloride or any other halogenated solvent.

CONFORMS TO

- **AMS 1526B (Partial Testing)**
- **BOEING BAC 5750**
- **BOEING D6-17487 REVISION "P"**
- **BOEING DPM 6561-2**

**NOTE: To place an order, call or FAX Customer Service at
800-932-7006 / FAX 1-216-441-1377
Cee-Bee A-954 Product Code # 24056**



NOTES PRIOR TO HANDLING

Before using your McGean-Rohco, Inc. products, all safety and operating instructions should be read and understood. If you have any questions, please contact your McGean-Rohco representative before proceeding.

USE PROCEDURES

With a water rinse:

1. Apply remover with mops or brushes.
2. Allow remover to dwell at least 5 minutes or until the coating is penetrated, then agitate the surface with a brush or mop.
3. Rinse thoroughly with high pressure water.

Without a water rinse:

1. Wipe surface clean, using clean cloths or nylon fleece scrubbing pads wet with cleaner. Turn frequently to prevent redeposition of soil or residues on cleaned surface.
2. Wipe with clean, dry cloths. If surface is to be air dried, all residual soil must be wiped.

PRECAUTIONS

- Contains concentrated solvents. Avoid eye and skin contact. Use rubber gloves and face shield or goggles. Some form of eye protection is always absolutely essential. Use with adequate ventilation.
- Do not use in confined areas. If ventilation is inadequate, use a niosh - certified respirator which will protect against organic vapor and dust/mist.
- Do not take internally. For contact with eyes or skin, flood with water. If eye irritation persists, seek medical attention. For inhalation, remove to fresh air.
- Store containers in a cool dry area. Open containers slowly to prevent any spewing of contents. Keep containers tightly sealed. Before using on plastic electrical insulation or a painted surface that might be damaged, check effect on samples.