

CEE-BEE INHIBITOR MX-15U

by Cee-Bee®



data sheet

CEE-BEE INHIBITOR MX-15U is a granular product used to inhibit oxidation of steel, aluminum, magnesium and other metals.

BENEFITS

- Increases inside storage time before oxidation occurs.
- Produces a film on iron and steel which prevents flash rusting.
- Does not interfere with paint adhesion.
- Economical no silicates, phosphates, chromates or other heavy metals.
- Contains no silicates, phosphates, chromates or other heavy metals.

NOTES PRIOR TO HANDLING

Before using your McGean-Rohco, Inc. products, all safety and operating instructions should be read and understood. If you have any questions, please contact your McGean-Rohco representative before proceeding.

**NOTE: To place an order, call or FAX Customer Service at
800-932-7006 / FAX 1-216-441-1377
Cee-Bee Inhibitor MX-15U Product Code # 26019**



USE PROCEDURES

1. Thoroughly dissolve 0.25 oz. to 1.0 oz Inhibitor per gallon of distilled or deionized water. Chlorides and other constituents of tap water tend to reduce protection.
2. After parts have been cleaned, spray on Inhibitor solution or use in a dip tank at ambient temperature (can be used at elevated temperatures, but effective tank life will be reduced). Allow parts to soak 3 to 5 min., drain well to remove excess solution from recesses and air dry.

PROPERTIES

- A free-flowing, white to yellow granular powder.

PRECAUTIONS

- Contains nitrites. Avoid contact with combustibles. Avoid eye contact and prolonged skin contact. Use goggles or face shield and rubber gloves. Do not take internally. For accidental contact, flush with water. If irritation persists, seek medical attention.
- Concentrations exceeding 1 ounce per gallon will result in a white powdery residue which will interfere with paint adhesion. Keep containers sealed to prevent moisture absorption.