

CEE-BEE WDO

by Cee-Bee®



d a t a s h e e t

CEE-BEE WDO is a high flash water displacing oil designed to provide anti-rust protection.

BENEFITS

- Quickly displaces water from metal surfaces.
- Effectively prevents flash rusting of ferrous parts after cleaning, stripping or pickling.
- Provides outstanding protection during indoor storage.
- The tack-free, semi-dry film does not collect excessive dust and soil.
- Safe on all common metals, and will not adversely affect well-bonded paints, most plastics, glass or masonry.
- Non-photochemically reactive.
- Low vapor toxicity.

CONFORMS TO

- **GENERAL ELECTRIC C02-064**
- **PRATT & WHITNEY SPMC 126 (SPOP 216)**
- **ROLLS ROYCE OMAT 1036**
- **INTERNATIONAL AERO ENGINE OMAT 10-091**

**NOTE: To place an order, call or FAX Customer Service at
800-327-0466 / FAX 1-216-441-1377
Cee-Bee WDO Product Code# 27009**



NOTES PRIOR TO HANDLING

Before using your McGean, Inc. products, all safety and operating instructions should be read and understood. If you have any questions, please contact your McGean-Rohco representative before proceeding.

USE PROCEDURES

Dip Tank

1. Immerse parts in undiluted Cee-Bee WDO at ambient temperature. The water displaced by the preferential wetting action of Cee-Bee WDO will settle at the bottom of the tank.
2. After about 10 to 60 seconds, remove the parts and allow excess Cee-Bee WDO to drain back into the tank.
3. Air dry.

Water, collected as an immiscible layer on the bottom of the tank, should be periodically drained off and fresh Cee-Bee WDO added to raise the volume.

Spray-on

1. Spray on undiluted Cee-Bee WDO at ambient temperature using non-atomizing spray equipment. Thoroughly wet the entire surface.
2. Allow parts to air dry.

Cee-Bee C-50 wipe solvent, Cee-Bee Cleaner R-679 solvent/emulsion cleaner, or Cee-Bee A-7X7 hot tank cleaner can be used to remove the Cee-Bee WDO protective film.

PRECAUTIONS

- Can cause eye and skin irritation - avoid contact. Use rubber gloves and face shield or goggles. Use with adequate ventilation.
- Do not take internally. In case of accidental contact with eyes or skin, flush thoroughly with water. If irritation persists, seek medical attention.

Copyright 1994 McGean-Rohco, Inc.
Revd. 6/05