

CEE-BEE BUBBLE FLUID F-19

by Cee-Bee®



d a t a s h e e t

CEE-BEE BUBBLE FLUID F-19 is a bubble fluid used for detecting leaks in high pressure and low pressure oxygen systems in aircraft

BENEFITS

- A convenient and effective leak detecting method.
- Leak areas easily located.
- Compatible with oxygen.
- Safe on most metals, including aluminum, steel and copper.
- Safe on good quality paint and most plastics.
- Non-flammable.
- Surfactants biodegradable.

CONFORMS TO

- **LOCKHEED EPS 31.211**
- **MIL-L-25567D, TYPE I**

**NOTE: To place an order, call or FAX Customer Service at
800-327-0466 / FAX 1-216-441-1377
Cee-Bee Bubble Fluid F-19 Product Code # 27031**



NOTES PRIOR TO HANDLING

Before using your McGean-Rohco, Inc. products, all safety and operating instructions should be read and understood. If you have any questions, please contact your McGean-Rohco representative before proceeding.

USE PROCEDURES

1. Apply a thin layer of bubble fluid by brush or from tip of plastic squeeze bottle to all fittings, connections and check valves. Leaks can be readily located by the formation of bubbles where the oxygen is escaping.
2. After inspection is complete, all bubble fluid must be completely removed from the surface. Thoroughly wipe surface with clean, damp cloths or rinse off with water.

PROPERTIES

- Water-white to amber, clear thin liquid.
- No flash point.

PRECAUTIONS

- Avoid eye contact and prolonged skin contact. May cause irritation. Do not take internally. In case of accidental contact with eyes, flood with water. If irritation persists, seek medical attention.