

## BASIC CHROMIC ACETATE POWDER

<b>FORMULA:</b>	$\text{Cr}_3(\text{OH})_2(\text{C}_2\text{H}_3\text{O}_2)_7 \cdot \text{XH}_2\text{O}$		
<b>TYPICAL ANALYSIS:</b>	Trivalent Chrome	Cr(III)	23.3 - 24.7%
	Basicity*		20 - 30%
	Chloride	Cl	0.10% Max
	Hexavalent Chrome	Cr (VI)	None Detected <0.0001%

**FORM:** Blue-Green Powder

**STANDARD PACKAGE:** 150 pound fiber drum; 4 per pallet

**APPLICATIONS:** Chrome Acetates are used in pigments, drilling muds, textile mordants, leather tanning, and as catalysts for oxidation, polymerization, and emulsion hardening.

\*Basicity Percent of charge on chrome displaced by hydroxyl ion.

35100  
CAS# 39430-51-8  
BJP/MFG  
04/01/14

BEFORE USING ANY OF THESE PRODUCTS, YOU MUST BECOME COMPLETELY FAMILIAR WITH THE SAFETY AND HAZARD INFORMATION CONTAINED IN OUR MATERIAL SAFETY DATA SHEETS. McGean (the Seller) presents the information without warranty and disclaims any liability arising from its use and misuse. Seller recommends use of the information and Seller's products solely in commercial processes which are specified by Seller and which do not violate any third-party patent rights or any laws or regulations. THE SELLER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE EXCEPT AS EXPRESSLY STATED IN THE SELLER'S SALES CONTRACT OR SALES ACKNOWLEDGEMENT FORM.