



CHROMIC CHLORIDE SOLUTION

FORMULA:	CrCl₃ in Water		
TYPICAL ANALYSIS:	Trivalent Chrome	Cr(III)	11.5 – 12.5%
	Basicity*		0% +/- 5%
	Hexavalent Chrome	Cr (VI)	None Detected <0.0001%

FORM: Dark Green Solution

STANDARD PACKAGE: 600 pound drum; 4 per pallet
55 pound plastic pail; 24 per pallet

APPLICATIONS: Chromic Chloride is used as an intermediate in the manufacture of chromium compounds, vapor chromium plating, waterproofing compounds, as a mordant in textile dyeing, and as a cross linking agent.

*Basicity Percent of charge on chrome displaced by hydroxyl ion

35430
CAS# 10025-73-7, 7647-01-0
BJP/MFG
04/01/14

BEFORE USING ANY OF THESE PRODUCTS, YOU MUST BECOME COMPLETELY FAMILIAR WITH THE SAFETY AND HAZARD INFORMATION CONTAINED IN OUR MATERIAL SAFETY DATA SHEETS. McGean (the Seller) presents the information without warranty and disclaims any liability arising from its use and misuse. Seller recommends use of the information and Seller's products solely in commercial processes which are specified by Seller and which do not violate any third-party patent rights or any laws or regulations. THE SELLER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE EXCEPT AS EXPRESSLY STATED IN THE SELLER'S SALES CONTRACT OR SALES ACKNOWLEDGEMENT FORM.